



Western 1-Kote Sanded

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Western 1-Kote Sanded

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wall Coating

1.3. Details of the supplier of the safety data sheet

Sacramento Stucco Co.
1550 Parkway Blvd.
West Sacramento, CA 95691
T 916-372-7442 - F 916-372-4836

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 4 (Oral) H302
Skin Irrit. 2 H315
Eye Dam. 1 H318
Carc. 1A H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302 - Harmful if swallowed
H315 - Causes skin irritation
H318 - Causes serious eye damage
H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P264 - Wash thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell
P302 + P352 - If on skin: Wash with plenty of water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - If exposed or concerned: Get medical advice/attention
P310 - Immediately call a poison center/doctor
P330 - Rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

Western 1-Kote Sanded

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Quartz	(CAS No) 14808-60-7	65 - 70	Acute Tox. 4 (Oral), H302 Carc. 1A, H350
Cement, portland, chemicals	(CAS No) 65997-15-1	25 - 30	Not classified
Calcium hydroxide	(CAS No) 1305-62-0	1 - 2	Not classified
Kaolin	(CAS No) 1332-58-7	<1	Not classified
Magnesium hydroxide	(CAS No) 1309-42-8	<1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Aluminosilicate glass	(CAS No) None	<0.5	Not classified
Glass, oxide, chemicals	(CAS No) 65997-17-3	<0.5	Carc. 1B, H350
Calcium formate	(CAS No) 544-17-2	0.1 - 0.5	Not classified
Silica, amorphous	(CAS No) 7631-86-9	<0.1	Not classified
Sodium hydroxide	(CAS No) 1310-73-2	<0.1	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Diatomaceous earth	(CAS No) 61790-53-2	<0.1	Not classified
Magnesium oxide (MgO)	(CAS No) 1309-48-4	<0.1	Not classified
Dolomite (CaMg(CO ₃) ₂)	(CAS No) 16389-88-1	<0.1	Not classified
Formaldehyde-naphthalenesulfonic acid polymer sodium salt	(CAS No) 9084-06-4	<0.1	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person immediately to fresh air. Consult a physician as necessary.
- First-aid measures after skin contact : Wash affected area with mild soap and water. If irritation persists, get medical attention.
- First-aid measures after eye contact : Flush immediately with water for at least 15 minutes. Do not rub eyes. If irritation persists get medical attention.
- First-aid measures after ingestion : Dilute by drinking large quantities of water. If discomfort persists, consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory stress from particulate inhalation.
- Symptoms/injuries after skin contact : Causes skin irritation. Contact with dry product on wet skin or contact with moist or wet product may cause more severe effects including thickening, cracking or fissuring of the skin. Prolonged contact can cause severe skin damage in the form of caustic chemical burns.
- Symptoms/injuries after eye contact : Causes eye irritation. Eye contact with dry product or splashes of wet product may cause chemical burns and blindness.
- Symptoms/injuries after ingestion : Not considered a likely route of entry under normal product use conditions. Ingestion of harmful amounts of dust may cause nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

Western 1-Kote Sanded

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Clean up immediately using shovel or scoop. Dispose of in accordance with local, state, and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes and skin. Keep in dry areas. Avoid inhalation of dust. Prolonged contact with wet product can cause serious, potentially irreversible skin or eye damage in the form of chemical burns.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep in closed, air-tight containers. Do not store in close proximity to acids.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Calcium hydroxide (1305-62-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Magnesium hydroxide (1309-42-8)		
ACGIH	Not applicable	
OSHA	Not applicable	
Magnesium oxide (MgO) (1309-48-4)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)
Dolomite (CaMg(CO ₃) ₂) (16389-88-1)		
ACGIH	Not applicable	
OSHA	Not applicable	
Kaolin (1332-58-7)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Cement, portland, chemicals (65997-15-1)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Western 1-Kote Sanded

Safety Data Sheet

Glass, oxide, chemicals (65997-17-3)		
ACGIH	Not applicable	
OSHA	Not applicable	
Silica, amorphous (7631-86-9)		
ACGIH	Not applicable	
OSHA	Not applicable	
Sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
OSHA	Not applicable	
Calcium formate (544-17-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
Diatomaceous earth (61790-53-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
Formaldehyde-naphthalenesulfonic acid polymer sodium salt (9084-06-4)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Use sufficient local exhaust to reduce the levels of respirable silica to below exposure limits. Minimize the build-up of dust on walls, floors, equipment, and other horizontal surfaces.
Hand protection	: Use neoprene or rubber gloves.
Eye protection	: Use safety glasses, goggles, or face shield under circumstances where particles could cause eye injury.
Skin and body protection	: Wear suitable working clothes.
Respiratory protection	: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: Dark grey
Odor	: None
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available

Western 1-Kote Sanded

Safety Data Sheet

Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity	: 2.95
Solubility	: Insoluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Dolomitic lime is alkaline and incompatible with acids, ammonium salts and phosphorus. A shortened shelf life is expected with exposure to air.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

Not determined

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Western 1-Kote Sanded	
ATE US (oral)	717.360 mg/kg body weight

Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
ATE US (oral)	7340.000 mg/kg

Silica, amorphous (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 2.2 mg/l (Exposure time: 1 h)

Sodium hydroxide (1310-73-2)	
LD50 dermal rabbit	1350 mg/kg
ATE US (dermal)	1350.000 mg/kg

Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
ATE US (oral)	500.000 mg/kg

Calcium formate (544-17-2)	
LD50 oral rat	2650 mg/kg
ATE US (oral)	2650.000 mg/kg body weight

Western 1-Kote Sanded

Safety Data Sheet

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Silica, amorphous (7631-86-9)	
IARC group	3 - Not classifiable

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Diatomaceous earth (61790-53-2)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Silica, amorphous (7631-86-9)	
LC50 fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)

Sodium hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

Calcium formate (544-17-2)	
LC50 fish 1	>= 1000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Calcium hydroxide (1305-62-0)	
BCF fish 1	(no bioaccumulation)

Dolomite (CaMg(CO₃)₂) (16389-88-1)	
BCF fish 1	(no known bioaccumulation)

Silica, amorphous (7631-86-9)	
BCF fish 1	(no bioaccumulation expected)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container in accordance with local/regional/national/international regulations.
--------------------------------	---

Western 1-Kote Sanded

Safety Data Sheet

SECTION 14: Transport information

In accordance with DOT
Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Calcium hydroxide (1305-62-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Magnesium hydroxide (1309-42-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Magnesium oxide (MgO) (1309-48-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Dolomite (CaMg(CO₃)₂) (16389-88-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Kaolin (1332-58-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Cement, portland, chemicals (65997-15-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Glass, oxide, chemicals (65997-17-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Silica, amorphous (7631-86-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Sodium hydroxide (1310-73-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quartz (14808-60-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Calcium formate (544-17-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Diatomaceous earth (61790-53-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Formaldehyde-naphthalenesulfonic acid polymer sodium salt (9084-06-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Quartz (14808-60-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Calcium hydroxide (1305-62-0)				
U.S. - Massachusetts - Right To Know List				
U.S. - Minnesota - Hazardous Substance List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				

Magnesium oxide (MgO) (1309-48-4)				
U.S. - Massachusetts - Right To Know List				
U.S. - Minnesota - Hazardous Substance List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				

Western 1-Kote Sanded

Safety Data Sheet

Kaolin (1332-58-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Cement, portland, chemicals (65997-15-1)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Glass, oxide, chemicals (65997-17-3)

U.S. - Minnesota - Hazardous Substance List

Silica, amorphous (7631-86-9)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Sodium hydroxide (1310-73-2)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Diatomaceous earth (61790-53-2)

U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H335	May cause respiratory irritation
H350	May cause cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product