



**WESTERN BLENDED  
PRODUCTS**  
The Plasterer's Standard

# Premium Acrylic Finish - Vera Stone

A 100% acrylic based interior & exterior decorative coating.



- 100% Acrylic Finish.
- Dirt Pickup Resistance Formula.
- Natural Color Aggregate



Use for:

AFC Acrylic Finish Coats



## Description:

Vera Stone is a blend of naturally occurring aggregates including mica, varying in color, shape, and size. Each particular blend resembles natural stone-like granite finishes. This homogenous mixture may be applied by hand trowel; it may be used to decorate interiors and other home accents such as: arches, columns, and even barbecues. After a short drying time, Vera Stone provides a dramatic appearance, all while delivering long-lasting durability. Much like the rock it imitates, Vera Stone provides a classic look for interior and exterior surfaces.

## Packaging:

PAF Vera Stone is packaged in a 60 Lb (27.21 Kgs) pail.

## Benefits and Use:

PAF Vera Stone is pre-mixed and ready to apply. PAF Nova Stone has excellent color retention and is also an extremely durable DPR architectural acrylic finish, which could be used in a variety of interior and exterior systems. Although PAF Vera Stone is recommended over Western 1-Kote exterior stucco systems previously prepared with BPS Super Fine Skim Coat, it can also be applied over properly prepared substrates such as masonry, concrete and other approved stucco systems.

## Coverage:

PAF Vera Stone covers approximate 95 sq. ft. when applied at (1/8") one-eighth of an inch.

## Preparation:

PAF Vera Stone must be applied over dry, clean surfaces, free of dust and imperfections. Basecoats receiving PAF Vera Stone shall be completely

cured for a minimum of 24 hours prior to application of PAF Vera Stone. If applied over concrete surfaces, concrete must be cured for a minimum of 28 days prior to application of PAF Vera Stone. All receiving substrates shall be coated with PAF Primer prior to PAF Vera Stone applications. PAF Primer must be dry before PAF Vera Stone is applied.

## Mixing:

PAF Vera Stone shall be mixed for 1 minute with a mixing blade powered by a 450-500 rpm drill, prior to application of the material. Do not overmix. A small amount of water may be added to adjust workability. Do not add more than 6 oz of water per pail.

## Application:

PAF Vera Stone is applied in a single coat process. Apply an even-thin coat using a steel trowel, not exceeding 1/8" in thickness. After the coat is applied, lightly float the surface with a plastic trowel. A float may be used to bring out the aggregate to the surface, cleaning the float several times in the process.

## Curing:

PAF Vera Stone drying is upon environment conditions. Under average conditions (70°F) PAF Vera Stone will dry in 48 hours. Lower temperature conditions require PAF Vera Stone to be covered or protected for longer periods.

## Limitations:

Surface temperatures shall not be below 50°F (10°C). Environment temperature must be between 50°F (10°C) and 90°F (32°C) for PAF Vera

Stone applications. Do not use PAF Vera Stone on exposed exterior horizontal surfaces. Do not apply PAF Vera Stone on surfaces that will receive sealant.

## Storage:

PAF Vera Stone should be stored in sealed containers avoiding sunlight and in temperatures above 40°F (4°C).

## Technical Testing Data:

Upon request.

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. **KEEP OUT OF REACH OF CHILDREN.**

## Warranty:

Manufacturers of Western Blended Products (WBP) warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WBP instructions. Manufacturers of WBP do not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at manufacturers of WBP option, to a refund of the purchase price. In the event of a claim under this warranty, written notice must be given to the originating plant of the WBP goods at the address shown hereon. This limited warranty is issued and accepted in lieu of all other expressed warranties, and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

DEC 2017

**Sacramento Stucco Co.**  
1550 Parkway Blvd., West Sacramento, CA 95691 / (916) 372-7442  
**Western Stucco Co.**  
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455  
**Rio Grande Stucco Co.**  
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

Visit us on the web:  
[westernblended.com](http://westernblended.com)



Western Blended Products are manufactured in the U.S.A. utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

