



# Western 1-Kote Premium Gray Concentrate


A fiber reinforced, enhanced performance modified portland cement basecoat for One-Coat & Conventional Stucco Systems



### Available Presentations:

- Standard Concentrate
- Premium Concentrate
- Sanded Versions

### Product Uses:



SB Stucco Basecoats

Available in:

### Description:

Western 1-Kote Premium Gray Concentrate is a fiber reinforced, modified portland cement exterior plaster formulated for enhanced performance characteristics. The product may be used in conjunction with various foam substrates to create wall assemblies with higher R-values and improved crack and water resistance. Western 1-Kote Premium Gray Concentrate may also be used over wood or gypsum backing and may be utilized for a scratch and/or brown coat application for a conventional stucco system.

Western 1-Kote Premium Gray Concentrate features a low shrinkage formulation, enhanced fiber content and accelerated set characteristics designed to improve crack resistance and finish readiness.

### Packaging:

- Western 1-Kote Premium Gray Concentrate is packaged in 80 lb / 36.29 kg bags.
- 40 bags per pallet.

### Product Uses:

Western 1-Kote Premium Gray Concentrate is intended for use as:

- A one-coat stucco basecoat over approved lath assemblies
- A scratch and/or brown coat in conventional stucco systems
- Application over approved substrates in accordance with IAPMO ER-382

### Benefits:

- Low shrinkage formulation designed to reduce drying shrinkage and enhance crack resistance characteristics.
- Enhanced fiber reinforcement for improved tensile strength and crack control.
- Reduced alkalinity profile (pH <10 at 3 days) to improve compatibility and readiness for application of suitable finish coats.
- Accelerated set characteristics with an approximate 40-minute working time under standard environmental conditions (70°F / 50% RH).
- May be utilized over a variety of substrates affording architects and builders design flexibility.
- Provides a cost-effective hard wall substrate with enhanced insulation characteristics when used in appropriate wall assemblies.
- May be used as a scratch and brown coat for conventional systems.

Pot life may vary depending on ambient temperature, substrate temperature and jobsite

conditions.

### Coverage:

- Approximately 72 square feet, 8 square yards, and 6.7 square meters @ 3/8" thickness
- Approximately 54 square feet, 6 square yards, and 5.0 square meters @ 1/2" thickness.

Coverage may vary depending on substrate condition, application method and waste.

### Mixing:

Western 1-Kote Premium Gray Concentrate is mixed with two hundred pounds (200 lb), approximately sixteen (16) #2 shovels, of ASTM rated plaster sand and approximately four (4) gallons of potable water.

Each sack shall mix for a minimum of five (5) minutes. Continuous batching is an acceptable practice. Care shall be taken to provide sufficient mixing time when additional sacks are added to a batch to ensure uniform consistency.

### Application:

Western 1-Kote Premium Gray Concentrate is applied by approved applicators. The material may be applied by hand or plaster pump. Specific minimum thickness is required for application over various substrates. Consult product specifications and the IAPMO Evaluation Report #382 for specific details.

The minimum thickness over any substrate, when used in conjunction with the Western 1-Kote System, is three-eighths (3/8") of an inch.

### Curing:

The product requires a minimum of forty-eight (48) hours moist curing. Environmental conditions such as heat, wind and low humidity will require additional curing.

### Finishing:

A variety of finishes such as Western Exterior Stucco, standard acrylic paint and Premium Acrylic Finish (PAF) may be applied over Western 1-Kote Premium Gray Concentrate. The recommendations of the finish coat manufacturer shall be followed regarding basecoat preparation, bonding, application and curing of their product.

### Limitations:

Do not apply when surface or ambient temperatures are at or below 40°F / 4.4°C or above 100°F / 38°C. Do not apply to surfaces that

are contaminated with bond breakers, oils or other matter that may affect the performance of the product. Do not apply Western 1-Kote Premium Gray Concentrate if conditions are expected to be above or below the specified temperature range within 24 hours of application. Do not add additional ingredients without specific written approval from an authorized manufacturer of Western Blended Products.

### Storage:

Western 1-Kote Premium Gray Concentrate shall be kept indoors or, if stored outdoors, shall be adequately covered to keep dry and stored off the ground.

### Applicable Standards, Specifications and Codes:

- IAPMO ER#382
- 2024, 2021, 2018 & 2015 International Building Code (IBC).
- 2024, 2021, 2018 & 2015 International Residential Code (IRC).
- 2025 & 2022 California Building Code (CBC).
- 2025 & 2022 California Residential Code (CBC).
- 2025 California Wildland-Urban Interface Code.
- 2023 Florida Building Code (FBC Building).
- 2023 Florida Building Code (FBC Residential).
- ASTM C926 — Application of Portland Cement-Based Plaster
- ASTM C1063 — Installation of Lathing and Furring

### Conditions of Use and Limited Warranty

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. KEEP OUT OF REACH OF CHILDREN.

Western Blended Products (WBP) warrants that its products are of merchantable quality and suitable for the general purpose for which they are intended when applied in accordance with WBP instructions. The manufacturers of WBP products do not warrant the products to be suitable for any purpose or use other than that for which they are intended. Liability under this warranty is limited to supplying new material without charge or, at the option of the manufacturer of the WBP product, refunding the purchase price. In the event of a claim under this warranty, written notice must be provided to the originating plant of the WBP product at the address shown herein. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts; therefore, the above limitations or exclusions may not apply.

REV 02.16.2026

**Sacramento Stucco Co.**  
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442

**Western Stucco Co.**  
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455

**Rio Grande Stucco Co.**  
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

**WESTERN BLENDED PRODUCTS**

[www.westernblended.com](http://www.westernblended.com)

For updated information, please visit our website.

Western Blended Products are manufactured in the U.S.A. & Mexico utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

