



**WESTERN BLENDED
PRODUCTS**
The Plasterer's Standard

Western Stucco-Patch Stuccolastic

An acrylic latex compound for portland cement,
concrete, stucco & masonry.



- SP Stucco Patching
- AP Acrylic Patching

Description:

Stuccolastic is an acrylic based, knife grade, polymer compound for patch and repair of hairline surface cracks up to 1/4" in depth and width. It may be applied over gypsum plasters, portland cement plasters and stucco and acrylic finishes.

Packaging:

Stuccolastic is packaged in two presentations:

- 1 Gal (12 Lbs / 5.44 Kg).
- 5 Gal (60 IBS / 27.20 Kg).

Benefits:

Stuccolastic it's excellent for crack repairs. It provides a durable, flexible matrix when properly applied that most paints will adhere to. Stuccolastic is ready to use. No mixing is required.

Sands Blends:

Stuccolastic is available in a "Smooth" and "Textured" finish.

Mixing:

No mixing is required. A small amount of water may be added to the pail if it has been opened and the material has thickened.

Application:

1. Use a margin trowel or putty knife to apply Stuccolastic. A narrower blade provides better pressure for filling the compound into the hairline cracks. Apply Stuccolastic in short passes perpendicular to the hairline cracks.
2. Once the crack is filled, draw the margin trowel or putty knife length wise over the top of the crack, applying additional pressure to fill Stuccolastic into the hairline crack.
3. Use a small paint brush and lightly brush Stuccolastic perpendicular to the crack in order to feather the material over the surface.

Curing:

Allow a minimum of 72 hours for the Stuccolastic to dry before application of primers, paints or acrylic finishes.

Finishing:

Most paints and acrylic finishes may bond to Stuccolastic. Coating manufactures have a wide variety of products. It is recommended that any coating being applied in a small test area to check adhesion before proceeding with the application of the coating.

Western Whitecap Bonder or similar products are required in portland cement base coats or colored finishes if applied over Stuccolastic.

Limitations:

Do not add accelerator, air entrainment or other admixtures to Stuccolastic without written permission from an authorized manufacturer of Western Blended Products.

Do not apply when surface or ambient temperatures are at or below 40°F / 4.4°C or above 100°F / 34°C. Do not apply to surfaces that are contaminated with bond breakers, oils or other matter that may affect the performance of the product. Do not apply Stuccolastic if conditions are expected to be above or below the specified temperature range within 24 hours of application. Do not add additional ingredients to Stuccolastic without specific written approval from an authorized manufacturer of Western Blended Products.

Storage:

Stuccolastic shall be kept indoors or if stored outdoors, shall be adequately covered to keep dry and be stored off the ground.

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. **KEEP OUT OF REACH OF CHILDREN.**

Warranty:

Manufacturers of Western Blended Products (WBP) warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WBP instructions. Manufacturers of WBP do not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at manufacturers of WBP option, to a refund of the purchase price. In the event of a claim under this warranty, written notice must be given to the originating plant of the WBP goods at the address shown hereon. This limited warranty is issued and accepted in lieu of all other expressed warranties, and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

DEC 2017

Sacramento Stucco Co.
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442
Western Stucco Co.
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455
Rio Grande Stucco Co.
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

Visit us on the web:
westernblended.com



Western Blended Products are manufactured in the U.S.A. utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

