



Blackcap Contractor Strength

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Blackcap Contractor Strength

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wall Coating

1.3. Details of the supplier of the safety data sheet

Sacramento Stucco Co.
1550 Parkway Blvd.
West Sacramento, CA 95691
T 916-372-7442 - F 916-372-4836

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Sens. 1 H317

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H317 - May cause an allergic skin reaction

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - If on skin: Wash with plenty of water
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Blackcap Contractor Strength

Safety Data Sheet

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	65 - 75	Not classified
Proprietary Acrylic Resin	Trade Secret	25 - 35	Not classified
Proprietary Surfactant	Trade Secret	0.5 - 10	Not classified
1,2-Benzisothiazolin-3-one	(CAS No) 2634-33-5	<1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
Lithium hydroxide monohydrate	(CAS No) 1310-66-3	<0.1	Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person immediately to fresh air. Consult a physician as necessary.
- First-aid measures after skin contact : Wash with soap and water. Wash contaminated clothing before reuse. Seek medical attention if irritation develops or persists.
- First-aid measures after eye contact : Flush with plenty of water for at least 15 minutes. Seek medical attention.
- First-aid measures after ingestion : Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Excessive exposure to vapors or spray mists may cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation or rash upon prolonged or repeated contact.
- Symptoms/injuries after eye contact : May cause irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use water, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Clean up with water before allowing to dry. Sodium chloride may be sprinkled on the spill, which may coagulate the latex and facilitate cleaning with water. Place coagulated waste in a closed container. Wear protected equipment during cleanup.
- Methods for cleaning up : Dispose of waste in accordance with local, state and federal regulations.

Blackcap Contractor Strength

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in a cool, dry, well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,2-Benzisothiazolin-3-one (2634-33-5)

ACGIH : Not applicable

OSHA : Not applicable

Lithium hydroxide monohydrate (1310-66-3)

ACGIH : Not applicable

OSHA : Not applicable

Proprietary Acrylic Resin

ACGIH : Not applicable

OSHA : Not applicable

Proprietary Surfactant

ACGIH : Not applicable

OSHA : Not applicable

Water (7732-18-5)

ACGIH : Not applicable

OSHA : Not applicable

8.2. Exposure controls

Appropriate engineering controls : General (mechanical) room ventilation is expected to be satisfactory for normal handling.

Hand protection : Use neoprene or rubber gloves.

Eye protection : Protective goggles.

Skin and body protection : Wear suitable working clothes.

Respiratory protection : None required under normal product handling conditions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Viscous.

Color : White

Odor : Slight Acrylic

Odor threshold : No data available

pH : 7.5 - 8

Melting point : No data available

Freezing point : <0 °C (<32 °F)

Boiling point : >100 °C (>212 °F)

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Blackcap Contractor Strength

Safety Data Sheet

Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Specific gravity	: 1.05
Relative vapor density at 20 °C	: No data available
Solubility	: Miscible with water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: 800 cP at 25°C (77 °F)
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Freezing temperatures (less than 32°F or 0°C).

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

Hydrocarbons and irritating, acrid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1,2-Benzisothiazolin-3-one (2634-33-5)	
LD50 oral rat	1020 mg/kg
ATE US (oral)	500.000 mg/kg body weight
Lithium hydroxide monohydrate (1310-66-3)	
LD50 oral rat	120 mg/kg
LC50 inhalation rat (mg/l)	0.96 mg/l/4h
ATE US (oral)	120.000 mg/kg body weight
ATE US (vapors)	0.960 mg/l/4h
ATE US (dust, mist)	0.960 mg/l/4h
Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Blackcap Contractor Strength

Safety Data Sheet

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1,2-Benzisothiazolin-3-one (2634-33-5)

Log Pow	1.3 (at 25 °C)
---------	----------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

1,2-Benzisothiazolin-3-one (2634-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.4. US State regulations

Lithium hydroxide monohydrate (1310-66-3)

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

Blackcap Contractor Strength

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H301	Toxic if swallowed
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H400	Very toxic to aquatic life
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product