



PAF Exterior Paint

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product name : PAF Exterior Paint

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wall Coating

1.3. Details of the supplier of the safety data sheet

Sacramento Stucco Co.
1550 Parkway Blvd.
West Sacramento, CA 95691
T 916-372-7442 - F 916-372-4836

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Carc. 1A H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H350 - May cause cancer

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P308+P313 - If exposed or concerned: Get medical advice/attention
- P405 - Store locked up
- P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Limestone	(CAS No) 1317-65-3	10 - 20	Not classified
Kaolin	(CAS No) 1332-58-7	0 - 10	Not classified
Quartz	(CAS No) 14808-60-7	0 - 10	Acute Tox. 4 (Oral), H302 Carc. 1A, H350
Titanium dioxide	(CAS No) 13463-67-7	0 - 10	Carc. 2, H351
Silica, amorphous	(CAS No) 7631-86-9	0 - 10	Not classified
Aluminum hydroxide (Al(OH) ₃)	(CAS No) 21645-51-2	0 - 10	Not classified
1,2-Propylene glycol	(CAS No) 57-55-6	0 - 10	Not classified
Attapulgite	(CAS No) 12174-11-7	0 - 10	Carc. 2, H351

PAF Exterior Paint

Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
Methacrylic acid	(CAS No) 79-41-4	0 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Immediate medical attention is not required. Get medical attention if symptoms occur. Call a physician if irritation develops or persists.
- First-aid measures after skin contact : Immediate medical attention is not required. Call a physician if irritation develops or persists.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician if irritation develops or persists.
- First-aid measures after ingestion : If swallowed, do not induce vomiting - seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : None under normal use.
- Symptoms/injuries after skin contact : None under normal use.
- Symptoms/injuries after eye contact : May cause eye irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of spill if safe to do so.
- Methods for cleaning up : Dispose of waste in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep in a dry, cool and well-ventilated place. Keep out of the reach of children. Store in accordance with local regulations. Keep from freezing.

PAF Exterior Paint

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)

Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)

Limestone (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Kaolin (1332-58-7)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Methacrylic acid (79-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm

8.2. Exposure controls

Appropriate engineering controls	: General (mechanical) room ventilation is expected to be satisfactory for normal handling.
Hand protection	: Use protective gloves to minimize skin contact.
Eye protection	: Protective goggles.
Skin and body protection	: Wear suitable working clothes.
Respiratory protection	: None required under normal product handling conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Color	: Off-white, gray or colored
Odor	: Faint
Odor threshold	: No data available
pH	: > 8
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: 0.96 - 1.8 g/cc
Relative vapor density at 20 °C	: No data available
Solubility	: Miscible with water.
Log Pow	: No data available

PAF Exterior Paint

Safety Data Sheet

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Do not freeze. To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
ATE US (oral)	500.000 mg/kg
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
LD50 oral rat	> 5000 mg/kg
Silica, amorphous (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 2.2 mg/l (Exposure time: 1 h)
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
1,2-Propylene glycol (57-55-6)	
LD50 oral rat	20 g/kg
LD50 dermal rabbit	20800 mg/kg
ATE US (oral)	20000.000 mg/kg body weight
ATE US (dermal)	20800.000 mg/kg body weight
Methacrylic acid (79-41-4)	
LD50 oral rat	1060 mg/kg
LD50 dermal rabbit	500 - 1000 mg/kg
LC50 inhalation rat (mg/l)	7.1 mg/l/4h
ATE US (oral)	1060.000 mg/kg body weight
ATE US (dermal)	500.000 mg/kg body weight
ATE US (vapors)	7.100 mg/l/4h
ATE US (dust, mist)	7.100 mg/l/4h

PAF Exterior Paint

Safety Data Sheet

Skin corrosion/irritation	: Not classified pH: > 8
Serious eye damage/irritation	: Not classified pH: > 8
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Silica, amorphous (7631-86-9)	
IARC group	3 - Not classifiable

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Attapulgate (12174-11-7)	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Silica, amorphous (7631-86-9)	
LC50 fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)

1,2-Propylene glycol (57-55-6)	
LC50 fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Silica, amorphous (7631-86-9)	
BCF fish 1	(no bioaccumulation expected)

1,2-Propylene glycol (57-55-6)	
BCF fish 1	< 1

Methacrylic acid (79-41-4)	
Log Pow	0.93

PAF Exterior Paint

Safety Data Sheet

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Aluminum hydroxide (Al(OH)₃) (21645-51-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silica, amorphous (7631-86-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Kaolin (1332-58-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2-Propylene glycol (57-55-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Methacrylic acid (79-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

PAF Exterior Paint

Safety Data Sheet

Attapulgite (12174-11-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Quartz (14808-60-7)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Silica, amorphous (7631-86-9)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Titanium dioxide (13463-67-7)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Limestone (1317-65-3)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Kaolin (1332-58-7)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

1,2-Propylene glycol (57-55-6)
U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Methacrylic acid (79-41-4)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H350	May cause cancer
H351	Suspected of causing cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product