



Stuccolastic (Smooth & Textured)

Safety Data Sheet

SECTION 1: Identification

1.1. Identification

Product name : Stuccolastic (Smooth & Textured)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wall Coating

1.3. Details of the supplier of the safety data sheet

Sacramento Stucco Co.
1550 Parkway Blvd.
West Sacramento, CA 95691
T 916-372-7442 - F 916-372-4836

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
Muta. 1B H340
Carc. 1A H350

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H340 - May cause genetic defects
H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - If on skin: Wash with plenty of water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

Stuccolastic (Smooth & Textured)

Safety Data Sheet

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	20-35	Not classified
Limestone	(CAS No) 1317-65-3	30-35	Not classified
Acrylic Polymers	Trade Secret	20 - 30	Not classified
Kaolin	(CAS No) 1332-58-7	1-5	Not classified
Titanium dioxide	(CAS No) 13463-67-7	1-5	Carc. 2, H351
1,2-Propylene glycol	(CAS No) 57-55-6	1-5	Not classified
Attapulgite	(CAS No) 12174-11-7	1-5	Carc. 2, H351
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	(CAS No) 55965-84-9	< 1	Not classified
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	(CAS No) 25265-77-4	< 1	Not classified
Naphtha, petroleum, hydrotreated heavy	(CAS No) 64742-48-9	< 1	Not classified
Quartz	(CAS No) 14808-60-7	< 1	Acute Tox. 4 (Oral), H302 Carc. 1A, H350
3,5,7-Triaza-1-azoniatricyclo[3.3.1.1 ^{3,7}]decane, 1-(3-chloro-2-propenyl)-, chloride	(CAS No) 4080-31-3	< 1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311
Sodium bicarbonate	(CAS No) 144-55-8	< 1	Not classified
1,3,5,7-Tetraazatricyclo[3.3.1.1(3,7)]decane	(CAS No) 100-97-0	< 1	Not classified
Methylene chloride	(CAS No) 75-09-2	< 1	Acute Tox. 4 (Oral), H302 Carc. 1B, H350
1,3-Dichloropropene	(CAS No) 542-75-6	< 1	Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 1B, H350

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove to fresh air.
First-aid measures after skin contact	: Wash affected area thoroughly with soap and water. Consult a physician if irritation persists.
First-aid measures after eye contact	: Flush eyes with running water for at least 15 minutes. Consult a physician if irritation persists.
First-aid measures after ingestion	: If swallowed, give at least two (2) glasses of water and consult a physician. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Dust from sanding can cause headache, nausea, and irritation of nose, throat or lungs.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
Explosion hazard	: None known.

5.3. Advice for firefighters

Protection during firefighting	: Firefighters should wear full protective gear.
--------------------------------	--

Stuccolastic (Smooth & Textured)

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Dispose of waste in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid generating dust.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acrylic Polymers

Not applicable

Water (7732-18-5)

Not applicable

Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Not applicable

Limestone (1317-65-3)

OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)

Kaolin (1332-58-7)

ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)

Quartz (14808-60-7)

ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)

Attapulgit (12174-11-7)

Not applicable

Titanium dioxide (13463-67-7)

ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)

Stuccolastic (Smooth & Textured)

Safety Data Sheet

Titanium dioxide (13463-67-7)		
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
3,5,7-Triaza-1-azoniatricyclo[3.3.1.1 ^{3,7}]decane, 1-(3-chloro-2-propenyl)-, chloride (4080-31-3)		
Not applicable		
1,3,5,7-Tetraazatricyclo[3.3.1.1(3,7)]decane (100-97-0)		
Not applicable		
1,3-Dichloropropene (542-75-6)		
ACGIH	ACGIH TWA (ppm)	1 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1 ppm
Methylene chloride (75-09-2)		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (ppm)	25 ppm
OSHA	OSHA PEL (STEL) (ppm)	125 ppm (see 29 CFR 1910.1052)
IDLH	US IDLH (ppm)	2300 ppm
Sodium bicarbonate (144-55-8)		
Not applicable		
1,2-Propylene glycol (57-55-6)		
AIHA	WEEL TWA (mg/m ³)	10 mg/m ³
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)		
Not applicable		
Naphtha, petroleum, hydrotreated heavy (64742-48-9)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls	: General (mechanical) room ventilation is expected to be satisfactory for normal handling.
Hand protection	: Use neoprene or rubber gloves to provide protection against wet material..
Eye protection	: In case of dust production: protective goggles.
Skin and body protection	: Wear suitable working clothes.
Respiratory protection	: None required under normal product handling conditions. If material is sanded or ground when dry, approved respirators for dust should be provided and used. As with any safety product, workers using respirators should be trained in the proper selection, use and care of such equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: Light pink
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available

Stuccolastic (Smooth & Textured)

Safety Data Sheet

Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Insoluble
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

Not determined.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LD50 oral rat	53 mg/kg
Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
ATE US (oral)	500.000 mg/kg
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
3,5,7-Triaza-1-azoniatricyclo[3.3.1.1^{3,7}]decane, 1-(3-chloro-2-propenyl)-, chloride (4080-31-3)	
LD50 oral rat	500 mg/kg
LD50 dermal rabbit	565 mg/kg
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	565.000 mg/kg body weight
1,3,5,7-Tetraazatricyclo[3.3.1.1(3,7)]decane (100-97-0)	
LD50 oral rat	9200 mg/kg
ATE US (oral)	9200.000 mg/kg body weight

Stuccolastic (Smooth & Textured)

Safety Data Sheet

1,3-Dichloropropene (542-75-6)	
LD50 oral rat	224 mg/kg
LD50 dermal rabbit	333 mg/kg
LC50 inhalation rat (mg/l)	2.7 - 3.07 mg/l/4h
ATE US (oral)	224.000 mg/kg body weight
ATE US (dermal)	333.000 mg/kg body weight
ATE US (vapors)	2.700 mg/l/4h
ATE US (dust, mist)	2.700 mg/l/4h

Methylene chloride (75-09-2)	
LD50 oral rat	1600 mg/kg
LC50 inhalation rat (mg/l)	53 mg/l (Exposure time: 6 h)
ATE US (oral)	1410.000 mg/kg body weight

Sodium bicarbonate (144-55-8)	
LD50 oral rat	4220 mg/kg
ATE US (oral)	4220.000 mg/kg

1,2-Propylene glycol (57-55-6)	
LD50 oral rat	20 g/kg
LD50 dermal rabbit	20800 mg/kg
ATE US (oral)	20000.000 mg/kg body weight
ATE US (dermal)	20800.000 mg/kg body weight

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
LD50 oral rat	3200 mg/kg
LD50 dermal rat	> 15200 mg/kg
LC50 inhalation rat (mg/l)	> 3.55 mg/l (Exposure time: 6 h)
ATE US (oral)	3200.000 mg/kg body weight

Naphtha, petroleum, hydrotreated heavy (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Attapulgite (12174-11-7)	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable
In OSHA Hazard Communication Carcinogen list	Yes

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

1,3-Dichloropropene (542-75-6)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Stuccolastic (Smooth & Textured)

Safety Data Sheet

Methylene chloride (75-09-2)	
IARC group	2A - Probably carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes
In OSHA Specifically Regulated Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

1,3,5,7-Tetraazatricyclo[3.3.1.1(3,7)]decane (100-97-0)	
LC50 fish 1	44600 - 55600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	29868 - 43390 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1,3-Dichloropropene (542-75-6)	
LC50 fish 1	1.52 - 2.68 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.063 - 0.129 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	0.211 - 0.271 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 2	0.09 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Methylene chloride (75-09-2)	
LC50 fish 1	140.8 - 277.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	1532 - 1847 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	262 - 855 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	190 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Sodium bicarbonate (144-55-8)	
LC50 fish 1	8250 - 9000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	2350 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1,2-Propylene glycol (57-55-6)	
LC50 fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
LC50 fish 1	30 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1,3-Dichloropropene (542-75-6)	
Log Pow	2.3
Methylene chloride (75-09-2)	
BCF fish 1	6.4 - 40
Log Pow	1.25
1,2-Propylene glycol (57-55-6)	
BCF fish 1	< 1
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
Log Pow	3.47 (at 25 °C)

Stuccolastic (Smooth & Textured)

Safety Data Sheet

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated for transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Kaolin (1332-58-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

3,5,7-Triaza-1-azoniatricyclo[3.3.1.1^{3,7}]decane, 1-(3-chloro-2-propenyl)-, chloride (4080-31-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

1,3,5,7-Tetraazatricyclo[3.3.1.1^(3,7)]decane (100-97-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3-Dichloropropene (542-75-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 0.1 %

Methylene chloride (75-09-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 0.1 %

Sodium bicarbonate (144-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2-Propylene glycol (57-55-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Stuccolastic (Smooth & Textured)

Safety Data Sheet

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Attapulgite (12174-11-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

1,3-Dichloropropene (542-75-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Methylene chloride (75-09-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	200 µg/day

Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Kaolin (1332-58-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

3,5,7-Triaza-1-azoniatricyclo[3.3.1.1^{3,7}]decane, 1-(3-chloro-2-propenyl)-, chloride (4080-31-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

Stuccolastic (Smooth & Textured)

Safety Data Sheet

1,3,5,7-Tetraazatricyclo[3.3.1.1(3,7)]decane (100-97-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

1,3-Dichloropropene (542-75-6)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Methylene chloride (75-09-2)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

1,2-Propylene glycol (57-55-6)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product