



# California 1 Kote

## Safety Data Sheet

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : California 1 Kote

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wall Coating

#### 1.3. Details of the supplier of the safety data sheet

Sacramento Stucco Co.  
1550 Parkway Blvd.  
West Sacramento, CA 95691  
T 916-372-7442 - F 916-372-4836  
www.westernblended.com

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Acute Tox. 4 (Oral) H302  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Carc. 1A H350

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302 - Harmful if swallowed  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H350 - May cause cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell  
P302+P352 - If on skin: Wash with plenty of water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a poison center or doctor  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P330 - Rinse mouth.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

# California 1 Kote

## Safety Data Sheet

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS US classification
Plaster of Paris	(CAS-No.) 26499-65-0	35 - 40	Not classified
Calcium magnesium hydroxide (CaMg(OH)4)	(CAS-No.) 39445-23-3	15 - 30	Not classified
Calcium magnesium hydroxide oxide (CaMg(OH)2O)	(CAS-No.) 58398-71-3	15 - 30	Not classified
Limestone	(CAS-No.) 1317-65-3	>= 22.5	Not classified
Calcium hydroxide	(CAS-No.) 1305-62-0	7.5 - 18	Not classified
Perlite	(CAS-No.) 93763-70-3	<= 5	Not classified
Quartz	(CAS-No.) 14808-60-7	0.000025 - 0.9	Acute Tox. 4 (Oral), H302 Carc. 1A, H350

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air.
- First-aid measures after skin contact : Wash affected area thoroughly with soap and water. Consult a physician if irritation persists.
- First-aid measures after eye contact : Flush eyes with running water for at least 15 minutes. Consult a physician if irritation persists.
- First-aid measures after ingestion : If swallowed, give at least two (2) glasses of water and consult a physician. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory stress from particulate inhalation.
- Symptoms/injuries after skin contact : Causes skin irritation. Contact with dry product on wet skin or contact with moist or wet product may cause more severe effects including thickening, cracking or fissuring of the skin. Prolonged contact can cause severe skin damage in the form of caustic chemical burns.
- Symptoms/injuries after eye contact : Causes eye irritation. Eye contact with dry product or splashes of wet product may cause chemical burns and blindness.
- Symptoms/injuries after ingestion : Not considered a likely route of entry under normal product use conditions. Ingestion of harmful amounts of dust may cause nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : None known.

### 5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Avoid release to the environment.

# California 1 Kote

## Safety Data Sheet

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Dispose of waste in accordance with local, state and federal regulations.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid generating dust.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Plaster of Paris (26499-65-0)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
Perlite (93763-70-3)		
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
Limestone (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
Calcium magnesium hydroxide (CaMg(OH) <sub>4</sub> ) (39445-23-3)		
Not applicable		
Calcium magnesium hydroxide oxide (CaMg(OH) <sub>2</sub> O) (58398-71-3)		
Not applicable		
Calcium hydroxide (1305-62-0)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls : General (mechanical) room ventilation is expected to be satisfactory for normal handling.  
Hand protection : Use neoprene or rubber gloves to provide protection against wet material..  
Eye protection : In case of dust production: protective goggles.  
Skin and body protection : Wear suitable working clothes.

# California 1 Kote

## Safety Data Sheet

Respiratory protection : None required under normal product handling conditions. If material is sanded or ground when dry, approved respirators for dust should be provided and used. As with any safety product, workers using respirators should be trained in the proper selection, use and care of such equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid  
Appearance : Powder.  
Color : White  
Odor : No data available  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Solubility : Soluble  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosive limits : No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

Will not occur.

#### 10.4. Conditions to avoid

None.

#### 10.5. Incompatible materials

Not determined.

#### 10.6. Hazardous decomposition products

None.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

# California 1 Kote

## Safety Data Sheet

Quartz (14808-60-7)	
ATE US (oral)	500 mg/kg

Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
ATE US (oral)	7340 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Calcium hydroxide (1305-62-0)	
BCF fish 1	(no bioaccumulation)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the ozone layer : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

## SECTION 14: Transport information

In accordance with DOT

Not a dangerous good as defined in transport regulations

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# California 1 Kote

## Safety Data Sheet

### Calcium magnesium hydroxide (CaMg(OH)4) (39445-23-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Calcium magnesium hydroxide oxide (CaMg(OH)2O) (58398-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Calcium hydroxide (1305-62-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. US State regulations

### Plaster of Paris (26499-65-0)

U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Perlite (93763-70-3)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Calcium hydroxide (1305-62-0)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
H302	Harmful if swallowed
H350	May cause cancer

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*