




**WESTERN BLENDED
PRODUCTS**
The Plasterer's Standard

Premium Acrylic Finish - Nova Stone

A 100% acrylic based interior & exterior decorative coating.



- 100% Acrylic Finish.
- Dirt Pickup Resistance Formula.
- Natural Color Aggregate.



AFC Acrylic Finish Coats



Description:

Nova Stone incorporates a cohesive blend of natural aggregate materials. This new addition to Western Blended Products creates the seamless look of granite but spreads like the traditional PAF. Nova Stone is a blend of naturally occurring organic materials including: visible quartz, mica chips, and other minerals, combined in a variety of ways for unique colors and finishes. Like other plaster products, Nova Stone may be applied to any surface by hand trowel. Nova Stone provides the aesthetic look of granite without the extensive weight or cost.

Packaging:

PAF Nova Stone is packaged is packaged in a 60 Lb (27.21 Kgs) pail.

Benefits and Use:

PAF Nova Stone is pre-mixed and ready to apply. PAF Nova Stone has excellent color retention and is also an extremely durable DPR architectural acrylic finish, which could be used in a variety of interior and exterior systems. Although PAF Nova Stone is recommended over Western 1-Kote exterior stucco systems previously prepared with BPS Super Fine Skim Coat, it can also be applied over properly prepared substrates such as masonry, concrete and other approved stucco systems.

Coverage:

PAF Nova Stone covers approximate 95 sq. ft. when applied at (1/8") one-eighth of an inch.

Preparation:

PAF Nova Stone must be applied over dry, clean surfaces, free of dust and imperfections. Basecoats receiving

PAF Nova Stone shall be completely cured for a minimum of 24 hours prior to application of PAF Nova Stone. If applied over concrete surfaces, concrete must be cured for a minimum of 28 days prior to application of PAF Nova Stone. All receiving substrates shall be coated with PAF Primer prior to PAF Nova Stone applications. PAF Primer must be dry before PAF Nova Stone is applied.

Mixing:

PAF Nova Stone shall be mixed for 1 minute with a mixing blade powered by a 450-500 rpm drill, prior to application of the material. Do not overmix. A small amount of water may be added to adjust workability. Do not add more than 6 oz of water per pail.

Application:

PAF Nova Stone is applied in a single coat process. Apply an even-thin coat using a steel trowel, not exceeding 1/8" in thickness. After the coat is applied, lightly float the surface with a plastic trowel. A float may be used to bring out the aggregate to the surface. Float lightly over the finished surface, cleaning the float several times in the process.

Curing:

PAF Nova Stone drying is upon environment conditions. Under average conditions (70°F) PAF Nova Stone will dry in 48 hours. Lower temperature conditions require PAF Nova Stone to be covered or protected for longer periods.

Limitations:

Surface temperatures shall not be below 50°F (10°C). Environment temperature must be between 50°F

(10°C) and 90°F (32°C) for PAF Nova Stone applications. Do not use PAF Nova Stone on exposed exterior horizontal surfaces. Do not apply PAF Nova Stone on surfaces that will receive sealant.

Storage:

PAF Nova Stone should be stored in sealed containers avoiding sunlight and in temperatures above 40°F (4°C).

Technical Testing Data:

Upon request.

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. **KEEP OUT OF REACH OF CHILDREN.**

Warranty:

Manufacturers or Western Blended Products (WBP) warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WBP instructions. Manufacturers of WBP do not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at manufacturers of WBP option, to a refund of the purchase price. In the event of a claim under this warranty, written notice must be given to the originating plant of the WBP goods at the address shown hereon. This limited warranty is issued and accepted in lieu of all other expressed warranties, and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

DEC 2017

Sacramento Stucco Co.
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442
Western Stucco Co.
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455
Rio Grande Stucco Co.
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

Visit us on the web:
westernblended.com



Western Blended Products are manufactured in the U.S.A. utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

