



WBR
WESTERN BLENDED PRODUCTS
EST. 1932

EZ Kote Stucco

A polymer modified cementitious skim, leveling and bonding coat for surface preparation



- Skim / Level Stucco
- Surface Preparation
- Bond EPS Shapes

Product Uses:



SBS Stucco Bond & Skim

Description:

EZ Kote is a polymer modified portland cement product designed to be used with conventional or one coat portland cement plaster wall systems. EZ Kote functions as a multi-use material for skim coating, surface leveling and bonding applications over cementitious substrates.

The material is formulated with a fine aggregate gradation to allow for tight, smooth finishes when applied as a skim coat, while maintaining sufficient body for leveling irregular surfaces. EZ Kote is used to create a uniform substrate over portland cement plaster prior to the application of finish coatings.

In addition to skim and leveling applications, EZ Kote may be used as a bonding material for EPS foam shapes where adhesion to approved substrates is required. The polymer modification enhances adhesion characteristics while maintaining compatibility with cementitious and polymer-based finish systems.

Features and Uses:

EZ Kote may be used for the following applications:

- Skim coating directly over portland cement plaster surfaces.
- Leveling and smoothing irregular cementitious substrates.
- Surface preparation prior to application of finish coatings.
- Bonding EPS foam shapes to approved substrates.

Benefits:

- Provides a smooth, uniform surface for finish applications.
- Polymer modification improves adhesion to cementitious substrates.
- Multi-use material for skim, leveling and bonding applications.
- Fine sand blend allows for tight, smooth finishes.
- Provides a suitable substrate for cementitious and polymer finish systems.

Packaging:

- EZ Kote is packaged in 50 lb / 22.7 kg sacks.
- 56 sacks per pallet.

Coverage:

- Skim / Level Application: Coverage is

approximately 70 to 90 square feet per bag depending on substrate condition and application thickness.

- Bonding Application: Coverage will vary based on substrate condition and application method. Full contact coverage is required when bonding EPS shapes.

Mixing:

Each 50 lb sack of EZ Kote is mixed with potable water in a clean pail and drill mixed with a paddle mixer. Initial mixing time is approximately 3 minutes or until the material is thoroughly wet. The material shall stand for 5 minutes. Add additional water as needed and mix for one minute or just the time required to disperse the additional water.

Application in Typical Stucco Systems:

- Application as a Skim Coat: Apply EZ Kote with a steel trowel over portland cement plaster surfaces. Smooth material with trowel to achieve a uniform surface.
- Application for Surface Leveling: Apply EZ Kote to irregular cementitious surfaces to establish a uniform plane prior to finish application.
- Application as EPS Adhesive: All surfaces to receive EPS shapes shall be moistened before application. The surface of the EPS shape shall be scored to provide mechanical key. Apply EZ Kote with a notched trowel to the back of the EPS shape. Coverage should be 100%. Press firmly into place. The application of fiberglass tape at joints is recommended.

Curing:

The product requires a minimum of forty-eight (48) hours moist curing. Environmental conditions such as heat, wind and low humidity will require additional curing.

Finishing:

Exterior Stucco Finish, Premium Acrylic Finish, standard acrylic paints, textured stucco or acrylic finishes, or elastomeric coatings may be applied over EZ Kote. The recommendations of the finish coat manufacturer shall be followed regarding base coat preparation, acceptable pH levels, bonding, application and curing of their finish.

Limitations:

- Do not apply EZ Kote on surfaces sloped less than 30 degrees or surfaces that are below grade or subject to hydrostatic pressure.
- Do not apply when surface or ambient temperatures are at or below 40°F (4.4°C) or above 100°F (34°C).
- Do not apply to surfaces that are contaminated with bond breakers, oils or other matter that may affect the performance of the product.
- Do not apply EZ Kote if conditions are expected to be above or below the specified temperature range within 24 hours of application.
- Do not add additional ingredients to EZ Kote without specific written approval from an authorized manufacturer of Western Blended Products.

Storage:

EZ Kote shall be kept indoors or if stored outdoors, shall be adequately covered to keep dry and be stored off the ground.

Applicable Standards, Specifications and Codes:

- ASTM C926
- ASTM C150
- ASTM C1063
- 2024 International Building Code (IBC)
- 2024 International Residential Code (IRC)

Conditions of Use and Limited Warranty

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. KEEP OUT OF REACH OF CHILDREN.

Western Blended Products (WBP) warrants that its products are of merchantable quality and suitable for the general purpose for which they are intended when applied in accordance with WBP instructions. The manufacturers of WBP products do not warrant the products to be suitable for any purpose or use other than that for which they are intended. Liability under this warranty is limited to supplying new material without charge or, at the option of the manufacturer of the WBP product, refunding the purchase price. In the event of a claim under this warranty, written notice must be provided to the originating plant of the WBP product at the address shown herein. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts; therefore, the above limitations or exclusions may not apply.

REV 03.19.2026

Sacramento Stucco Co.
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442
Western Stucco Co.
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455
Rio Grande Stucco Co.
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

WBR
WESTERN BLENDED PRODUCTS
www.westernblended.com
For updated information, please visit our website.

Western Blended Products are manufactured in the U.S.A. & Mexico utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

